


ONYX COPILOT

Flexible LED reading light




20 lm

Pleasantly warm and glare-free light



37 cm

370 mm neck length powered via cigarette lighter or with a plastic base for fixed connection



12 V + 24 V

The stylish light is suitable for both passenger cars (12 volt) and trucks (24 volt)



Precisely illuminating vehicle interiors

With its elegant and dynamic design, the ONYX COPILOT LED reading light achieves seamless integration into vehicle interiors. With its high flexibility, the reading light has a wide range of options for illuminating specific areas of the vehicle interior. The neck of the light is made of matt black silicon rubber and can be individually adjusted. The LED lifetime of ONYX COPILOT is extremely long: up to 20,000 hours! The Luminaire can be switched on/off and remain connected permanently. OSRAM provides a 2 year guarantee for this stylish light.

Technical data

Product information

Application (Category and Product specific)	Flexible LED reading light
---	----------------------------

General Product Information

Global order reference	ONYXCOPILOT L+7
------------------------	-----------------

Electrical Data

Nominal voltage	12/24 V
-----------------	---------

Photometric Data

Color temperature	3200 K
Nominal luminous flux	20 lm

Physical Attributes & Dimensions



Product weight	72.00 g
----------------	---------

Colors & materials

Base color	Black
------------	-------

Additional product data

Connector to lamp	Cigarette lighter plug
-------------------	------------------------

Capabilities

Technology	LED
------------	-----

Certificates & standards

Standards	CE
-----------	----

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Primary article identifier	4052899414938
Candidate list substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe use instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration no. in SCIP database	abeee974-0574-456e-82ec-afd9be936f89

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899414938	ONYX COPILOT	Folding carton box 1	110 mm x 35 mm x 290 mm	1.12 dm ³	153.00 g
4052899414945	ONYX COPILOT	Shipping carton box 4	149 mm x 118 mm x 302 mm	5.31 dm ³	730.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

File	
	User instruction UI LED ONYX COPILOT L
	User instruction LED ONYX COPILOT L
	User instruction GPRS_Safety symbols instructions

References / Links

Guarantee terms are available at www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

