

LEDiving PREMIUM Festoon

Ideal replacement for any vehicle




Wide range of different light colors

Available in Warm White and Cool White for a variety of customization options



Excellent brightness

Thanks to advanced thermal management and superior light distribution



Matches 31 mm, 36 mm & 41 mm festoon types

Upgrade to LED with simple plug & play replacement



Suitable LED replacement for Festoon Types

These LEDiving PREMIUM products offer a suitable replacement for festoon lamps. The lamps are compatible with conventional festoon lamp bases and are easy to install through plug & play. Thanks to modern diffusor material the lamps provide a perfect light distribution. OSRAM offers a 6 year guarantee for these festoon retrofit lamps. These products are not ECE-approved and must not be used on public roads in any exterior application. Use on public roads will invalidate both the operating license and insurance coverage. Some countries prohibit the sale and use of these products. Please contact your local distributor for information on your country.

Product family datasheet

Technical data

Product description	Electrical Data				Photometric Data	
	Power input	Nominal voltage	Nominal wattage	Test voltage	Nominal luminous flux	
LEDiving PREMIUM Festoon $\triangleq$ C5W	1.75 W	12 V	1 W	13.5 V	35 lm	
LEDiving PREMIUM Festoon $\triangleq$ C5W	1.75 W	12 V	1 W	13.2 V	35 lm	
LEDiving PREMIUM Festoon $\triangleq$ C5W	1.75 W	12 V	1 W	13.5 V	35 lm	
LEDiving PREMIUM Festoon $\triangleq$ C5W	1.75 W	12 V	0 W	13.5 V	35 lm	

Product description	Luminous flux tolerance	Physical Attributes & Dimensions	Lifetime Data		Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)
		Diameter	Lifespan B3	Lifespan Tc	Primary article identifier
LEDiving PREMIUM Festoon $\triangleq$ C5W	$\pm 30\%$	11.0 mm	2500 hr	5000 hr	4062172173933 4062172267304 4052899068469 4052899435377 4052899435353 4052899486850 4052899068551 4062172328111 4052899435391 4062172054065
LEDiving PREMIUM Festoon $\triangleq$ C5W	$\pm 30\%$	11.0 mm	2500 hr	5000 hr	4008321876140 4008321684141 4008321658159
LEDiving PREMIUM Festoon $\triangleq$ C5W	$\pm 30\%$	11.0 mm	2500 hr	5000 hr	4052899068612 4052899068506
LEDiving PREMIUM Festoon $\triangleq$ C5W	$\pm 30\%$	11.0 mm	2500 hr	5000 hr	4052899276000 4062172173858 4052899436077 4052899436053 4052899068483 4052899068582 4052899436091

Product family datasheet

Product description	Candidate list substance 1	CAS No. of substance 1	Safe use instruction	Declaration no. in SCIP database
LEDiving PREMIUM Festoon ≙ C5W	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	31d7a82b-9761-47ca-9bf9-8a1b06269b30 489c1c3d-f4c1-4ffd-bd83-7592feca468c 170341f6-451b-44d7-9c96-59d90d26f3c3 863bd28f-1c19-449c-b58f-ab245ca4c1ea 8d7c66e0-2314-4620-8048-229940a06ca7 5b652795-46c4-48a3-94c6-7ec8345541e9 969147cb-6cd7-44a7-956a-615f4ffaf571 84959c7d-1865-4163-b37a-e0e3a1df04c5
LEDiving PREMIUM Festoon ≙ C5W	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	bb2718cd-aa21-4320-892b-2a15b0681fe6 48c99376-e992-46b7-b608-db51e5462774 20f0758e-d0f9-4fc9-bf71-94af616baec0
LEDiving PREMIUM Festoon ≙ C5W	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	5a525071-52c5-419d-8110-3d385a2c332c 9ea5aef6-ae09-445d-a03c-359750906da5
LEDiving PREMIUM Festoon ≙ C5W	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	43511214-9e1f-420c-942a-e6c632f48904 a03e1707-99ab-4a22-8acf-8ba7e955a3e7 32bb19fb-18ff-493d-a361-f5b3d548f7ca 359b941c-54c8-49d4-a006-decde7162bee 9fe1fe62-fcfa-481b-b17b-04fce3c098be be2a7d6a-aa46-416f-8b8e-54bc5a9dc6 a7bae958-155d-4e0d-9396-c98552ae2223

Download Data

File	
	User instruction GPRS_Safety symbols instructions
	Brochures LEDriving Retrofits - Exchange overview (EN)
	ref_pim_amsproduct360degreeimages LEDriving PREMIUM SL C5W 6497CW
	ref_pim_amsproduct360degreeimages LEDriving PREMIUM SL C5W 6499WW WARM WHITE
	ref_pim_amsproduct360degreeimages LEDriving PREMIUM SL C5W 6499CW

Legal advice

These products are not ECE-approved and must not be used on public roads in any exterior application.

Use on public roads will invalidate both the operating license and insurance coverage.

Some countries prohibit the sale and use of these products. Please contact your local distributor for information on your country. Detailed guarantee terms can be found at www.osram.com/am-guarantee. LEDriving CANBUS CONTROL UNIT avoids error messages on the board computer when using LED based products. Compared with conventional lamps

References / Links

Guarantee terms are available at www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

