

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikaflex®-522



Revision Date: 03.07.2026

Version 2.4

Print Date 03.07.2026

Date of last issue: 03.12.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikaflex®-522

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Sealant/adhesive

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Norge AS
Sanitetsveien 1
2013 Skjetten
Telephone : +47 67 06 79 00
E-mail address of person : kundeservice@no.sika.com
responsible for the SDS

1.4 Emergency telephone number

Giftinformasjonen: 22 59 13 00

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture according to Regulation (EC) No. 1272/2008.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture according to Regulation (EC) No. 1272/2008.

Additional Labelling

EUH208 Contains trimethoxyvinylsilane, 2-octyl-2H-isothiazole-3-one (OIT). May produce an allergic reaction.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikaflex®-522



Revision Date: 03.07.2026

Version 2.4

Print Date 03.07.2026

Date of last issue: 03.12.2025

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Contains a biocide in order to protect the product. Active ingredient: 2-octyl-2H-isothiazole-3-one (OIT), 26530-20-1. Please use treated articles responsibly.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Urea,N,N''-(methylenedi-4,1-phenylene)bis[N'-butyl-	77703-56-1 416-600-4 01-0000016345-72-XXXX	Aquatic Chronic 4; H413	>= 2,5 - < 5
trimethoxyvinylsilane Contains: tetramethyl orthosilicate <= 0,2 %	2768-02-7 220-449-8 014-049-00-0 01-2119513215-52-XXXX	Flam. Liq. 3; H226 Acute Tox. 4; H332 Skin Sens. 1B; H317 Acute toxicity estimate Acute inhalation toxicity (vapour): 16,8 mg/l	>= 0,5 - < 1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikaflex®-522



Revision Date: 03.07.2026

Version 2.4

Print Date 03.07.2026

Date of last issue: 03.12.2025

2-octyl-2H-isothiazole-3-one (OIT)	26530-20-1 247-761-7 613-112-00-5 01-2120768921-45-XXXX	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 3; H311 Skin Corr. 1; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH071 M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100 specific concentration limit Skin Sens. 1A; H317 >= 0,0015 % Acute toxicity estimate Acute oral toxicity: 125 mg/kg Acute inhalation toxicity (dust/mist): 0,27 mg/l Acute dermal toxicity: 311 mg/kg	>= 0,0002 - < 0,0015
Substances with a workplace exposure limit :			
Titanium dioxide (> 10 µm)	13463-67-7 236-675-5 022-006-00-2 01-2119489379-17-XXXX		>= 2,5 - < 5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : No hazards which require special first aid measures.

If inhaled : Move to fresh air.

In case of skin contact : Take off contaminated clothing and shoes immediately.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikaflex®-522



Revision Date: 03.07.2026

Version 2.4

Print Date 03.07.2026

Date of last issue: 03.12.2025

Wash off with soap and plenty of water.

In case of eye contact : Remove contact lenses.
Keep eye wide open while rinsing.

If swallowed : Do not induce vomiting without medical advice.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : See Section 11 for more detailed information on health effects and symptoms.

Risks : No known significant effects or hazards.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : For personal protection see section 8.

6.2 Environmental precautions

Environmental precautions : No special environmental precautions required.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Wipe up with absorbent material (e.g. cloth, fleece).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikaflex®-522



Revision Date: 03.07.2026

Version 2.4

Print Date 03.07.2026

Date of last issue: 03.12.2025

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.
No special handling advice required.
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage : Keep container tightly closed in a dry and well-ventilated areas and containers place. Store in accordance with local regulations.

Advice on common storage : No special restrictions on storage with other products.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
Titanium dioxide (> 10 µm)	13463-67-7	TWA	5 mg/m3	FOR-2011-12-06-1358

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
methanol	67-56-1	TWA	200 ppm 260 mg/m3	2006/15/EC
	Further information: Indicative, Identifies the possibility of significant uptake through the skin			
		TWA	100 ppm 130 mg/m3	FOR-2011-12-06-1358
	Further information: The EU has set an indicative limit value and/or a remark for this substance, Chemicals that can be absorbed through the skin.			

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Appropriate engineering controls

Maintain air concentrations below occupational exposure standards.

Ensure adequate ventilation, especially in confined areas.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikaflex®-522



Revision Date: 03.07.2026

Version 2.4

Print Date 03.07.2026

Date of last issue: 03.12.2025

Individual protection measures, such as personal protective equipment (PPE)

- | | | |
|--------------------------|---|---|
| Eye/face protection | : | Safety glasses |
| Hand protection | : | Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
Butyl rubber/nitrile rubber gloves (> 0,1 mm)
Recommended: Butyl rubber/nitrile rubber gloves. |
| Skin and body protection | : | Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work. |
| Respiratory protection | : | In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
organic vapor filter (Type A)
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used. |

Environmental exposure controls

- | | | |
|----------------|---|--|
| General advice | : | No special environmental precautions required. |
|----------------|---|--|

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- | | | |
|----------------|---|------------|
| Physical state | : | liquid |
| Form | : | paste |
| Colour | : | various |
| Odour | : | very faint |

Melting point/ range / Freezing point	:	No data available
---------------------------------------	---	-------------------

Boiling point/boiling range	:	No data available
-----------------------------	---	-------------------

Flammability (solid, gas)	:	No data available
---------------------------	---	-------------------

Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit	:	No data available
--	---	-------------------

Lower explosion limit / Lower flammability limit	:	No data available
--	---	-------------------

Flash point	:	> 101 °C Method: closed cup
-------------	---	--------------------------------

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikaflex®-522



Revision Date: 03.07.2026
Date of last issue: 03.12.2025

Version 2.4

Print Date 03.07.2026

Auto-ignition temperature : No data available
Decomposition temperature : No data available
pH : Not applicable
substance/mixture is non-soluble (in water)

Viscosity

Viscosity, kinematic : > 20,5 mm²/s (40 °C)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-octanol/water : No data available

Vapour pressure : 0,01 hPa

Density : ca. 1,385 g/cm³ (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

: methanol

:

No hazardous decomposition products are known.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikaflex®-522



Revision Date: 03.07.2026

Version 2.4

Print Date 03.07.2026

Date of last issue: 03.12.2025

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Components:

Urea,N,N''-(methylenedi-4,1-phenylene)bis[N'-butyl-:

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg
Method: OECD Test Guideline 402

trimethoxyvinylsilane:

Acute oral toxicity : LD50 Oral (Rat): ca. 7.120 mg/kg

Acute inhalation toxicity : LC50: ca. 16,8 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute toxicity estimate: 16,8 mg/l
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : LD50: 3.540 mg/kg

2-octyl-2H-isothiazole-3-one (OIT):

Acute oral toxicity : Acute toxicity estimate: 125 mg/kg
Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008

Acute inhalation toxicity : Acute toxicity estimate: 0,27 mg/l
Test atmosphere: dust/mist
Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008

Acute dermal toxicity : Acute toxicity estimate: 311 mg/kg
Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008

Skin corrosion/irritation

Not classified due to lack of data.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikaflex®-522



Revision Date: 03.07.2026

Version 2.4

Print Date 03.07.2026

Date of last issue: 03.12.2025

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration hazard

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Not classified due to lack of data.

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Urea,N,N''-(methylenedi-4,1-phenylene)bis[N'-butyl-:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 250 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l
aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : EC50 (Raphidocelis subcapitata (freshwater green alga)): >
plants 100 mg/l
Exposure time: 72 h

2-octyl-2H-isothiazole-3-one (OIT):

M-Factor (Acute aquatic tox- : 100
icity)

M-Factor (Chronic aquatic : 100
toxicity)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikaflex®-522



Revision Date: 03.07.2026

Version 2.4

Print Date 03.07.2026

Date of last issue: 03.12.2025

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : There is no data available for this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

14.1 UN number or ID number

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikaflex®-522



Revision Date: 03.07.2026

Version 2.4

Print Date 03.07.2026

Date of last issue: 03.12.2025

ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA	:	Not regulated as a dangerous good
14.2 UN proper shipping name		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA	:	Not regulated as a dangerous good
14.3 Transport hazard class(es)		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA	:	Not regulated as a dangerous good
14.4 Packing group		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA (Cargo)	:	Not regulated as a dangerous good
IATA (Passenger)	:	Not regulated as a dangerous good
14.5 Environmental hazards		
Not regulated as a dangerous good		
14.6 Special precautions for user		
Not applicable		
14.7 Maritime transport in bulk according to IMO instruments		
Not applicable for product as supplied.		

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable
Schedules of Toxic Chemicals and Precursors

REACH Information: All substances contained in our Products are
- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 40: 1-methoxy-2-propanol

Number on list 75

REACH - Candidate List of Substances of Very High : None of the components are listed
(=> 0.1 %).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikaflex®-522



Revision Date: 03.07.2026

Version 2.4

Print Date 03.07.2026

Date of last issue: 03.12.2025

Concern for Authorisation (Article 59).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
Not applicable

Volatile organic compounds : Ordinance on the Incentive Tax on Volatile Organic Compounds (OVOC)
Volatile organic compounds (VOC) content: 0,03% w/w
no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 0,03% w/w

Other regulations:

Note the Working Environment Act § 4-1 and § 4-2 on requirements for the employer to protect pregnant employees against discomfort and injury as a result of the work situation and the working environment.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H226	:	Flammable liquid and vapour.
H301	:	Toxic if swallowed.
H311	:	Toxic in contact with skin.
H314	:	Causes severe skin burns and eye damage.
H317	:	May cause an allergic skin reaction.
H318	:	Causes serious eye damage.
H330	:	Fatal if inhaled.
H332	:	Harmful if inhaled.
H400	:	Very toxic to aquatic life.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikaflex®-522



Revision Date: 03.07.2026

Version 2.4

Print Date 03.07.2026

Date of last issue: 03.12.2025

- H410 : Very toxic to aquatic life with long lasting effects.
H413 : May cause long lasting harmful effects to aquatic life.

Full text of other abbreviations

- Acute Tox. : Acute toxicity
Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard
Eye Dam. : Serious eye damage
Flam. Liq. : Flammable liquids
Skin Corr. : Skin corrosion
Skin Sens. : Skin sensitisation
2006/15/EC : Europe. Indicative occupational exposure limit values
FOR-2011-12-06-1358 : Norway. Occupational Exposure limits
2006/15/EC / TWA : Limit Value - eight hours
FOR-2011-12-06-1358 / TWA : Long term exposure limit
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS : Chemical Abstracts Service
DNEL : Derived no-effect level
EC50 : Half maximal effective concentration
GHS : Globally Harmonized System
IATA : International Air Transport Association
IMDG : International Maritime Code for Dangerous Goods
LD50 : Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50 : Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL : International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL : Occupational Exposure Limit
PBT : Persistent, bioaccumulative and toxic
PNEC : Predicted no effect concentration
REACH : Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC : Substances of Very High Concern
vPvB : Very persistent and very bioaccumulative

Further information

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

|| Changes as compared to previous version !

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikaflex®-522



Revision Date: 03.07.2026

Version 2.4

Print Date 03.07.2026

Date of last issue: 03.12.2025

NO / EN